



QUATTRO by MENATWORK

S.C. QUATTRO PAVIMENTE TEHNICE S.R.L. - Șoseaua de Centură a Municipiului București, Nr. 103, Popești Leordeni, Județ Ilfov, Cod Poștal 077160, România
Tel: (004) 021.5296.200; 021.5296.231; 021.5288.344; 021.5288.336; Fax: (004) 021.5296.201; 021.5296.202; www.quattropavimente.ro; office@quattropavimente.ro;
Capital social: 118.000 RON; RC: J23/1196/2005; CIF: RO17712070; Cont IBAN: RO86FNNB001402986716RO01; Credit Europe Bank, Sucursala Militari, București

QUATTRO ACCESS FLOOR – Storage instructions

Please keep the floor on pallets with factory plastic protection until the moment of installation. The panels identification etiquette will be preserved from deterioration.

The access floor elements will be stored in indoor, closed and dry spaces, with normal humidity 40-65% and temperature between 15° and 35° C. AT ANY TIME THE FLOOR WILL BE PROTECTED AGAINST WATER OR HUMIDITY CONDITIONS. DANGER of floor deterioration.

In the storage room, the panels will be positioned minimum 20 cm away from the walls or vertical objects. DANGER of deterioration when lifter handling.

It is recommended that floor to be stored in spaces close to the installation area, with similar thermal and humidity characteristics.

QUATTRO PAVIMENTE SUPRAINALTATE SRL