

Chic UX+ C_{fl}-s1

5/64" velours bedrukt	5/64" velours imprimé	5/64" bedruckter Velours	5/64" printed cut-pile
100% polyamide IMPREL®	100% polyamide IMPREL®	100% Polyamid IMPREL®	100% nylon IMPREL®
RUG Vilt	DOSSIER Feùtre	RÜCKEN Vlies	BACKING Feltback
POOLHOOGTE ± 5 mm	HAUTEUR DU VELOURS ± 5 mm	POLHÖHE ± 5 mm	PILE HEIGHT ± 5 mm
TOTALE HOOGTE ± 8 mm	HAUTEUR TOTALE ± 8 mm	GESAMTHÖHE ± 8 mm	TOTAL HEIGHT ± 8 mm
POOLGEWICHT ± 580 g/m ²	POIDS DU VELOURS ± 580 g/m ²	POLGEWICHT ± 580 g/m ²	PILE WEIGHT ± 580 g/m ²
TOTAAL GEWICHT ± 1.590 g/m ²	POIDS TOTAL ± 1.590 g/m ²	GESAMTGEWICHT ± 1.590 g/m ²	TOTAL WEIGHT ± 1.590 g/m ²
AANTAL NOPPEN/M² ± 308 000	NOMBRE DE POINTS/M² ± 308 000	NOPPEN/M² ± 308 000	TUFT DENSITY/M² ± 308 000
AANBEVOLEN LEGWIJZE • Spannen op klitband • Universele fixeerlijm • Verhuislijm	POSE PRÉCONISÉE • Tendre sur bandes autogrippantes • Produit de maintien • Fixateur	EMPFOHLENE VERLEGEART • Verspannen auf Klettband • Universalfixierung • Wiederaufnahmeklebstoff	INSTALLATION METHOD • Stretched on hook tape • Release bond
GEBRUIK • Klasse 22+: Huishoudelijk • Comfort: 2 • Trappen (wonen) • Antistatisch • Brandkl. C _{fl} -s1 EN 13501-1 • Geschikt v. vloerverwarming	UTILISATION • Classe 22+: Domestique général • Confort: 2 • Escaliers (Habit.) • Antistatique • Classem. feu C _{fl} -s1 EN 13501-1 • Compatible avec sol chauffant • Résistance thermique: ISO 8302: 0.13 m ² K/W	EINSATZ • Klasse 22+: stark • Komfort: 2 • Treppeneignung (W) • Antistatisch • Baustoffkl. C _{fl} -s1 EN 13501-1 • Geeignet f. Fussbodenheizung • Wdw. ISO 8302: 0.13 m ² K/W	USAGE • Class 22+: General domestic • Comfort: 2 • Stairs domestic • Antistatic • Fire resist. C _{fl} -s1 EN 13501-1 • Suitable f. floorheating

Onder voorbehoud van wijzigingen van de technische specificaties - Sous réserve de modifications techniques - Unter Vorbehalt von technischen Änderungen - All rights reserved to alter technical specification




Chic	24	85	87	93	97	110	116	127	143	144	165	178	194
ULTRATEX QUICK+ CA 4M	•	•	•	•	•	•	•	•	•	•	•	•	•
ULTRATEX QUICK+ CA 5M	•	•	•	•	•	•	•	•	•	•	•	•	•



Chic ux+




400+500 cm 143



400+500 cm 165



400+500 cm 144




400+500 cm 178



400+500 cm 87



00+500 cm 85



400+500 cm 110



400+500 cm 116



400+500 cm 127




400+500 cm 24



400+500 cm 93



400+500 cm 194



400+500 cm 97

ITC _ Kanegemstraat 15 _ 8700 Tielt _ Belgium
 TEL. +32 51 42 44 11 FAX +32 51 42 44 85
 Email: itc@baltagroup.com www.baltagroup.com

