

## Technical specifications

# GRABOFLEX 256/T

### floor covering

### 1. Technical specifications

**Issued by:** Grabo Flooring-, Wallpaper and Artificial Leather Manufacturing Ltd.  
**Purpose:** technical requirements defining the quality of coated fabrics in rolls

### 2. Main characteristics

**Designations:** sports-flooring, flame retardant on flameproof concrete subfloor  
**Film:** PVC  
**Substrate:**

### 3. Technical Data of the Product

Parameter	Specification	Tolerance	Test method
Thickness mm	<b>6,0</b>	+ -0,2	MSZ EN 428
Linear change in dimensions % - length	<b>+ -0,4</b>	max.	MSZ EN 434
Linear change in dimensions % - cross	<b>+ -0,4</b>	max.	MSZ EN 434
Residual indentation mm	<b>0,35</b>	max.	MSZ EN 433
Peel resistance N/50mm - length	<b>50</b>	min.	MSZ EN 431
Peel resistance N/50mm - cross	<b>50</b>	min.	MSZ EN 431
Colour-fastness to light	<b>6</b>	min.	ISO 105 B02 3
Chemical resistance - 50% ethyl alcohol contact time 120 min	<b>no change</b>	appr.	MSZ EN 423
Chemical resistance - 5% fatty alcohol sulphonate contact time 120 min	<b>no change</b>	appr.	MSZ EN 423
Chemical resistance - 5% acetic acid contact time 120 min	<b>no change</b>	appr.	MSZ EN 423
Chemical resistance - petrol contact time 120 min	<b>no change</b>	appr.	MSZ EN 423
Wear layer thickness mm	<b>0,7</b>	min.	MSZ EN 429
Weight g/m <sup>2</sup>	<b>3740</b>	appr.	MSZ EN 430

**Valid from:**  
2000.04.20.

**Approved by:**  
Takács Árpád Leader of Quality Assurance