





features and benefits of all our underlays:

- 1. Offers superior comfort throughout your home
- 2. Guaranteed for the lifetime of the carpet
- 3. Protects your carpet from premature wear
- 4. Excellent heat and sound insulation
- 5. Recycled and recyclable
- An environmentally responsible product made in the LIK
- 7. Carpenter underlays are permeable and may be layed over a wood block floor

Specification:*

Classified to BS 5808: 1991 (2005)

Heavy Contract Use Suitable for stretch fit and double stick installations

Typical Values

Roll Length: 11m min
Roll Width: 137 cms +/- 1%
Roll Size: 15m² +/- 1%

Density: 145 kg/m³ + 5% - 0% Roll Weight: 16 kg +/- 5% Thickness: 7mm +/- 5%

Hot Metal Nut Test : BS 4790 : 1987 (2003) Classified to BS 5287 : 1988 : Low Radius

Thermal Resistance: 2.3 Tog

Decibel Reduction Delta Lw : 36 dB

Doublestick Castor Wheel Chair Test :

25000 + Revolutions

* Whilst every effort is made to ensure its accuracy, the data on this sheet is meant for information purposes only. The typical properties listed are the result of extensive laboratory tests, but since Carpenter has n control over the end use of each material, we cannot guarantee these results are obtained in practice. Users should conduct their own tests to determine the suitability of each material to its intended application.



For further details contact:

Carpenter Ltd, Dinting Lodge Industrial Estate, Glossop, Derbyshire, SK13 6LE.
Tel: +44 (0)1457 861141 • Fax: +44 (0)1457 863242 • Fmail: glossop,sales@carpenter.com

www.carpenter.ltd.uk