



# Lexa

Item number: 25861



## Technical Sheet

<b>Width</b>	approx. 140 cm
<b>Weight</b>	approx. 250 g/m <sup>2</sup>
<b>Repeat</b>	no repeat
<b>Composition</b>	100% Polyester FR
<b>Flame retardant</b>	DIN 4102/B1, M1, BS 5867 TYP B, IMO Res. A471 (XII), C1 Flame-resistance is dependant of foam that is used. note 5-6
<b>Lightfastness</b> DIN EN ISO 105-B02	note 4-5
<b>Fastness to Washing 40°</b> DIN EN ISO 105-C10	warp approx. +/-1%, weft approx. +/-1 %
<b>Fabric relaxing washing 40°C</b> DIN EN ISO 6330/DIN EN ISO 5077	warp approx. +/-1%, weft approx. +/-1 %
<b>Fabric relaxing dry cleaning</b> DIN EN ISO 3175-1	dry: note 4-5, wet: note 4-5
<b>Rub Fastness</b> DIN EN ISO 105-X12	approx. 20000 rubs
<b>Scrub resistance Martindale</b> DIN EN ISO 12947-2 / DIN EN 14465-2006	note 3-4 at 2000 rubs
<b>Pilling</b> DIN EN ISO 12945-2	
<b>Care</b>	

State: 27.05.2013

The above technical data are average values. These values only describe the technical characteristics and the chemical composition of the delivered goods. Warranties are not given.

