

# 113 Master Trax™



## Standard colours:



## Special colours:



- Durable carpet flooring, designed for large indoor entrance areas, including wall-to-wall applications. Offers many possibilities for creative combinations that will allow the entrance become part of the complete interior design.
- Unsurpassed ability to retain moisture and scrape debris from foot traffic while maintaining its great looking appearance for the longest time.
- Mold and mildew resistant, UV stabilized, crush resistant and remains unaffected by climate extremes.
- Suitable for even the heaviest of traffic conditions.
- For placement inside entrances or outside if not exposed to rain.
- In recess frames (depth 10 mm) or wall to wall installations in shopping malls, airports, hospitals, hotel lobbies, banks, restaurants, golf facilities (spikes resistant), fitness centers, elevators, locker rooms, ski lodges, skating rinks, automobile showrooms, any public of professional building.
- Vacuum/shampooing or use extraction method to clean.

PRODUCT SPECIFICATIONS		
Designation	Dust Control Matting	
Description	Absorbent / scrape carpet mat	
Material		
	Top	Nibbed needle punched carpet consisting of anti-static 100% polypropylene fibers. 1700 grams of yarn per m <sup>2</sup>
	Backing	Synthetic rubber (rolls), bitumen (tiles)
Process	Non woven/Needle punched	
Category	Indoor absorbent - Contract	
Recommended use	Indoor - heavy traffic areas - recess frames, wall to wall, finished mat	
Standard colours	Blue, Brown, Charcoal, Red, Natural, Grey, Autumn Black, Autumn Brown	
Special colours	Autumn Ochre , Royal-Blue, Burgundy, Green, Autumn Green, Autumn Burgundy	
Weight	3.2 kg/m <sup>2</sup>	
Thickness	11 mm	
Standard sizes	Full rolls: 200 cm x 21 m	
Custom sizes	200 cm per linear meter	
Special remarks	Crush resistant and unaffected by climate extremes. Mold/mildew resistant Easy to install, can be cut to any size or shape without edge ravel.	

## PRODUCT TESTING

Tests	Norms	Results
Abrasion resistance	ASTM D3884	
Colour fastness to light	AATCC 16E	
Accelerated wear test by sim floor machine	U.S.	
Accelerated soiling	U.S.	
Anti-slip	DIN51130 BGR181	
Water retention	U.S.	4 l/m <sup>2</sup>
Sanitary epidemiologic test	GN 2.1.6.1338-03 MCL GN 2.1.6.2309-07 OBUV	Pass - Certificate no. 77.01.16.229.P.044984.07.09

## FIRE TESTING

	Surface Flammability	ASTM D2859	Pass
	Classification of the reaction to fire performance	DIN EN 13501-1	
	Russian fire retardancy test	CCPB.NLOP-019.B01723	Pass

Sustainability	<ul style="list-style-type: none"> <li>• Recyclable materials</li> <li>• REACH compliant ( Registration, Evaluation, Authorization and restrictions of Chemicals)</li> <li>• Contributes to cleaner environment by reducing need of cleaning chemicals</li> </ul>
----------------	---