389 Swisslon Plus™



- Plush entrance matting with exceptional scraping and unsurpassed water absorbing qualities (5.5 litres per m²) for large indoor entrance areas, including wall-to-wall applications and stairs.
- Course yarns provide superb scraping and absorbing of dirt and moisture. Stylish yet subtle chevron pattern or streaked pattern versions hide dirt to maintain their elegant appearance.
- A dense heavyweight vinyl backing ensures longevity.
- Suitable for heavy traffic conditions.
- For placement in recess frames (depth 7 mm) or wall to wall installations in larger entrances at hotels, shopping malls, cinemas, public buildings, department stores, banks, restaurants and on stairs.
- Vacuum/shampooing or use injection/ extraction method periodically.



389 Swisslon Plus™

			PRODUCT SPEC	
Designation		Dust Control Matting		
Description		Absorbent carpet mat		
Material				
	Тор	Densely tufted cut loc 900 grams of yarn per		
	Backing	Black vinyl (DOP free)		
Process		Tufted		
Category		Indoor absorbent - Contract		
Recommended use		Indoor - heavy traffic conditions		
Colours		Wave Charcoal, Wave Red, Wave Taupe Twine Charcoal, Twine Red, Twine Taup		
Weight		3.5 kg/m ²		
Thickness		8.5 mm		
Standard sizes		130 cm x 20 m 200 cm x 20 m		
Custom sizes		130 cm and 200 cm pe	er linear meter	
Special rer	narks			
			PRODUCT 1	
	T	ests	N	
Abrasion resistance			ASTM D3884	
Colour fastness to ligh		nt	AATCC 16E	
		by sim floor machine	U.S.	
Accelerate	ed soiling		U.S.	
Anti-slip			DIN51130 BGR181	
Water rete	ention		U.S.	
Sanitary e	pidemiologi	c test	GN 2.1.6.1338-0 GN 2.1.6.2309-0	
Graves tea	r strength			
Hardness				
Elongation				
			FIRE TES	
		Surface Flammability	ASTM D2859	
		Russian fire	COLUMNI DZOSA	
		retardancy test		
		Classification of the reaction to fire performance	ISO EN 9239	
Sustainability			 Recyclable r REACH com and restricti Contributes chemicals 	



CIFICATIONS

ts per m²) consisting of 100% polyamide yarns

, Wave Blue, Wave Grey, Wave Black e, Twine Blue, Twine Grey, Twine Black

TESTING		
orms	Results	
	5	
	5.5 l/m ²	
3 MCL 7 OBUV		
TING		

Cfl-S1

material

pliant (Registration, Evaluation, Authorization

tions of Chemicals)

s to cleaner environment by reducing need of cleaning

www.notrax.eu