

HETEROGENEOUS
COMPACT VINYL

New Acczent Terra

CERTIFICATION & CLASSIFICATION	STANDARDS	New Acczent Terra
Classification	ISO 10874 – EN 685	Commercial: 34 Industrial: 43
Type of floor covering	ISO 10582 – EN 649	Heterogeneous Compact Vinyl. Type I.
TECHNICAL CHARACTERISTICS	STANDARDS	New Acczent Terra
Total thickness	ISO 24346 – EN 428	2.0 mm
Wear layer thickness	ISO 24340 – EN 429	0.8 mm
Total weight/m²	ISO 23997 – EN 430	2800 g
Surface treatment		PUR
TECHNICAL PERFORMANCES	STANDARDS	New Acczent Terra
Residual indentation	ISO 24343-1 – EN 433	≤ 0.10 mm
Reaction to fire	EN 13501-1	Class B _{f1} s1
Abrasion	EN 660-2	Group T: ≤ 2,0 mm ³
Slip resistance	DIN 51130 EN 13893	R10 ≥ 0.3
Dimensional stability	ISO 23999 – EN 434	≤ 0.10 % for rolls
Furniture leg	EN 424	No damage
Castor chair test	ISO 4918 – EN 425	No damage
Curl resultant to heat	ISO 23999 - EN 434	≤ 8 mm
Electrostatic properties	EN 1815	≤ 2 kV
Electrical resistance	EN 1081	≤ 10 ⁹ Ω
Light fastness	EN ISO 105-B02	≥ level 6
Chemical resistance	ISO 26987 – EN 423	Resistance
Hygiene		Does not contribute to infection spreading
TVOC after 28 days	ISO 16000	< 100 µg/m ³
Underfloor heating		Suitable – max 27°C
Form of delivery	ISO 24341 – EN 426 Sheet (rolls)	Approx. 23 running meters x 200 cm
Colours		19