599 Oct-O-Flex™



- Small holes diameter 14 mm, compliant with EU norm for public entrances, this rubber mat is designed to function at the immediate entrance, primarily as a scraper mat to stop dirt, grit and grime outside the doorway.
- No bumpy surface, ideal for carts, wheel chairs etc.
- Also available with molded rubber ramps.
- Its superior rubber compounds is made to withstand weather extremes and the heaviest of foot traffic
- Raised knobs underneath allow excellent drainage, leaving a clean and dry surface.
- Optional aluminium ramp kit (Alu Ramp Kit™) or placed in a recess frame.
- Outdoor entrances Heavy foot traffic areas
- Custom sizes available.
- Hose off with water.



599 Oct-O-Flex™

		PRODUCT SPECIFICATIONS	
Designation	Dust Control Matting		
Туре	Non-absorbent/ scrape rubber mat		
Description	Octogonal ring design with open construction		
Material	Natural rubber compound		
Process	Compression moulding		
Category	Outdoor Non absorbent - Rubber classics		
Recommended use	Outdoor - medium to heavy foot traffic		
Colours	Black		
Weight	10,3 kg/m ²		
Thickness	12,5 mm		
Standard sizes	75 cm x 100 cm 100 cm x 150 cm		
Custom sizes	Per m ²		
Special remarks	Suitable for use under extreme weather Accessories: Connectors Small holes diameter 14 mm, compliant with EU norm for public entrances		
		PRODUCT TESTING	
Tests		Norms	Results
Abrasion resistance		ASTM D3884	
Colour fastness to light		AATCC 16E	
Accelerated wear test by sim floor machine		U.S.	
Accelerated soiling		U.S.	
Anti-slip		DIN51130 BGR181	
Water retention		U.S	
Hardness		U.S	
Sanitary epidemiologic test		GN 2.1.6.1338-03 MCL GN 2.1.6.2309-07 OBUV	Pass - Certificate no. 77.01.16.251.P.044985.07.09
		FIRE TESTING	
	Surface Flammability	ASTM D2859	
	Classification of the reaction to fire performance	DIN EN 13501-1	
Sustainability		 Recyclable material REACH compliant (Registration, Evaluation, Authorization and restrictions of Chemicals) Contributes to cleaner environment by reducing need of cleaning chemicals 	

