



Indoor/Outdoor - Heavy traffic

692 Master Flex HHP™ D12

692 Master Flex HHP™ D12 high heel modular rubber mat tile for use with high heels has an open construction with tiny drainage holes and a depth of 12 mm.

The Master Flex HHP™ high heel modular entrance matting system has a stylish octagonal grooved design and tiny integrated holes combined with a densely tufted carpet insert to reduce the risk of trips and falls with high heels. Plus, its smooth surface makes it EU compliant for public entrances and suitable for wheeled access (carts, wheelchairs, suitcases, etc).

The Master Flex HHP™ C12 can be combined with the Master Flex HHP™ D12 for a harmonious transition from outdoor to indoor.

Recommended use:

- Heavy traffic
- For placement in interior or exterior recessed matwell frames

Specifications:

- Natural rubber
- Attachable bevelled edges are available
- Overall thickness: 12 mm
- Weight: 2.5 kg/m²
- Special characteristics: Free of DOP, free of DMF, free of ozone depleting substances, free of silicone and free of heavy metals
- Suitable for use in extreme weather
- Tiny drainage holes diameter 3 mm, specially designed for high heels, compliant with EU norm for public entrances

Recommended accessories:

• 597 Master Flex D12/C12™ Nitrile Safety Ramps

Standard sizes:

• 50 cm x 50 cm

Colours:

Black

Cleaning instructions:

· Hose off with water

PRODUCT TESTING
























692 Master Flex HHP™ D12


Art. nr.	Dimensions	Weight kg
692S0000OB	per m²	21.16
692S0050OB	50 cm x 50 cm	2.5



Recommended accessories: • 597 Master Flex D12/C12™ Nitrile Safety Ramps



Modular matting:
• Custom designs for any specific work station are possible and you will receive a CAD drawing for approval.



692 Master Flex HHP™ D12

GENERAL DESCRIPTION

Designation	Dust Control Matting	
Туре	Indoor / Outdoor - Modular Entrance Mat Systems	
Description	High heel modular rubber mat tile for use with high heels has an open construction with tiny drain-	
	age holes and a depth of 12 mm.	
Surface	Octagonal grooved design with tiny integrated holes	
Category	Dust Control Matting	
Recommended use	Indoor/Outdoor Heavy traffic	
Colours	Black	
Special remarks	Designed for pedestrian traffic. Not suitable for carts with extremely heavy loads.	
Edges	Attachable bevelled edges are available	

TECHNICAL SPECIFICATIONS

Material	Natural rubber	
Process	Compression Moulding	
Total weight	2.5 kg/m ²	
Overall thickness	12 mm	

DIMENSIONS

Standard sizes	Full rolls	Custom lengths
50 cm x 50 cm		

